



บริษัท เซอร์นิค อินเตอร์เนชั่นแนล จำกัด
CERNIC INTERNATIONAL CO.,LTD

Top Loading Kilns



KILN DETAILS								ELECTRICAL DETAILS		
TYPE	CAPACITY (LITRES/CU. FT.)	FIRING CHAMBER		OVERALL DIMENSIONS			WEIGHT	POWER (Kw.)	SUPPLY	
		DIAMETER	HEIGHT	WIDTH	DEPTH	HEIGHT			220V	380/415V
CN34	34/1.2	343 mm 13.5"	343 mm 13.5"	520 mm 20.5"	600 mm 23.5"	571 mm 22.5"	33 KGS 72 LBS	3.50	20A	-
CN74	74/2.6	457 mm 18"	457 mm 18"	648 mm 25.5"	724 mm 28.5"	686 mm 27"	50 KGS 110 LBS	7.00	40A	-
CN112	112.3/4.0	457 mm 18"	686 mm 27"	648 mm 25.5"	724 mm 28.5"	914 mm 36"	64 KGS 140 LBS	9.00	50A	20 A
CN223	223.6/7.9	660 mm 26"	680 mm 26.5"	895 mm 35"	965 mm 38"	940 mm 37"	92 KGS 202 LBS	13.00	70A	30A